

流量選定チャート

■ 口径15/20AフロコンAB用 20mmコンポジット・カートリッジ

Y-Type

ΔP: 20-130 kPa (15-130 kPa)*

型番	1Y0000	1Y0002	1Y0004	1Y0006	1Y0008
	グレイ*	アカ	アオ	クロ	ミドリ
L/min	1	2	3	4	5
0.486	1				
0.798	2				
1.050	3				
1.332	4				
1.886	5				
2.118	6				
2.298	7				
2.586	8				
2.700				3	
3.450		4			
3.714			4		
4.014				4	
5.532		5			
5.868					1
6.300		6			
6.816		7			
6.918			5		
7.098					2
7.164		8			
8.148					3
8.202			6		
8.298					4
8.736			7		
8.766			8		
9.282				5	
10.58				6	
10.78				7	
11.59				8	
13.84					5
14.23					6
15.15					7
16.40					8

設定流量

G-Type

ΔP: 40-400 kPa (30-400 kPa)*

型番	1G0001	1G0003	1G0005	1G0007	1G0009
	グレイ*	アカ	アオ	クロ	ミドリ
L/min	1	2	3	4	5
0.702	1				
1.134	2				
1.482	3				
1.950	4				
2.832	5				
3.168	6				
3.384			3		
3.582				3	
3.834	7				
4.164	8				
4.686		4			
5.448			4		
5.748				4	
8.214		5			
8.814					1
9.684		6			
10.40		7			
10.87			5		
10.88		8			
11.17					2
12.58					3
12.98			6		
13.09			7		
13.20			8		
14.21				5	
14.48					4
15.95				6	
16.13				7	
16.63				8	
21.92					5
22.15					6
23.51					7
24.47					8

設定流量

精度 +/- 5~10%